

Heavy-Duty Industrial Pedestal Fan

J&D's Heavy-Duty Industrial Pedestal Fan is an efficient and portable air circulator. It's perfect for keeping machinery and employees cool in the warm summer heat.

Features

- Heavy gauge, corrosion-resistant, powder coated fan guards, base, and pole
- Pedestal pole has a chrome insert tube to adjust the center height of the fan from 3'10" to 5'2"
- Direct drive and quiet operation
- Wide, low profile base with 4" rubber wheels to easily transport the fan
- Attached cord with 3-prong plug pre-wired for 115 Volts
- Available in oscillating models with an 80° pivot range, or non-oscillating models
- 3-blade aluminum propeller
- 30" oscillating fan has ½ HP high output performance motor
- Guard meets OSHA 1910.212(a)(5) requirements
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, and are covered by a **2 Year Warranty**

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/ Watt	Drive	Prop
Single Phase							
Non-Oscillating							
VDF20WB2	20"	1	2(H)	2,550	13.3	Direct	3-Alm
			(L)	1,900	12.7		
VDF24WB2	24"	1	2(H)	3,700	15.5	Direct	3-Alm
			(L)	2,050	13.0		
Oscillating							
VDF201WB2	20"	1	3(H)	2,340	13.0	Direct	3-Alm
			(M)	2,280	20.4		
			(L)	2,250	23.2		
VDF241WB2	24"	1	3(H)	3,820	15.7	Direct	3-Alm
			(M)	3,350	20.2		
			(L)	3,050	21.5		
* VDF301WB2	30"	1	3(H)	6,520	14.0	Direct	3-Alm
			(M)	6,060	14.9		
			(L)	4,970	13.2		

* Experts choice

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

**Wheels
for easy
transport**



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.