

60" Premium Indoor/Outdoor UL507 Ceiling Fan

The J&D Indoor/Outdoor Ceiling Fan provides a healthier environment with constant circulation dissipating gases and other odors, keeping the air cooler and fresher while drying walls and floors. In the summer, the fan creates a mild wind chill to gently cool. It vertically mixes warm stagnant air and disperses hot pockets which can be a breeding ground for germs and bacteria. In the winter, the fan prevents warm air from collecting in the rooftop and peaks to reduce condensation that drips down on surfaces.

Features

- Designed for high-humidity and high-moisture applications
- UL/CUL certified (file # E130543) for outdoor and agricultural use
- Passed UL/CUL water spray test and corrosion test
- Completely sealed motor and housing
- Switch on fan allows you to reverse operation for upward or downward airflow
- 23" cord with 3-prong plug pre-wired for 115 Volts
- 10" down rod (total fan height is 21")
- High output curved steel blades
- Simple J-Hook Mount
- Corrosion-resistant white powder coated finish
- Energy efficient 9,415 CFM of air movement using less energy than a 100 Watt light bulb
- Mixes air to save you money on heating and cooling bills

Part#	Size	Ph	Spd	Thrust CFM	Drive	Prop
Single Phase						
CF60A	60"	1	1/Var^	9,415	Direct	3-Stl
Recommended Variable Speed Controls (Not Included)						
CN25	2 Fan Speed Control, 120 Volts, 2.5 Amps					
CN5	4 Fan Speed Control, 120 Volts, 5 Amps					
VFT130144	8 Fan Speed Control, 120 Volts, 10 Amps					
CN15	12 Fan Speed Control, 120 Volts, 15 Amps					

^ Variable speed fans require separate variable speed control to adjust fan speed



Smooth • Quiet • Efficient

Fiberglass Funnel Fan

Fiberglass Funnel Fans by J&D Manufacturing come equipped with a maintenance-free, energy-efficient motor and powder coated heavy-duty mounting bracket. The durable fiberglass housing provides increased stability over regular poly funnel fans.

Features

- Directional fan with unique housing shape throws air twice as far as conventional circulation fans to move air into the corners of your building
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings and are covered by a **2 Year Warranty**
- Gold Star Motors are IP66-Rated

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
Single Phase							
VU20F2-GS	20"	1	1	4,330	7.7	Direct	3-Alm

* Experts choice

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12
 OSHA requires this fan to be mounted a minimum of 7' above the floor

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
Single Phase							
VU16F	16"	1	1	1,680	6.3	Direct	3-Alm
VU20F2	20"	1	1	2,870	12.8	Direct	3-Alm

*



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.